



# product\_datasheet\_title

## ENDURA Classic Beam Wall UpDown GU10

ENDURA® BEAM | GU10 socketed luminaires with classic shape and light outlet up and down



## technical\_data

## ELECTRICAL DATA


Nominal voltage	220...240 V
Mains frequency	50...60 Hz
Protection class	I
Operating mode	Mains voltage

## PHOTOMETRICAL DATA

Photobiological safety group acc. to EN62778	RG1
Photobiological safety group acc. to EN62471	RG0

## DIMENSIONS &amp; WEIGHT

Length	104.00 mm
Width	92.00 mm
Height	200.00 mm
Product weight	791.00 g



ENDURA CLASSIC BEAM  
UPDOWN GU10 DG

## MATERIALS &amp; COLORS

Product color	Dark gray
Housing color	Dark gray
Body material	Aluminum
Cover material	Glass
Mercury content	0.0 mg

## APPLICATION &amp; MOUNTING

Type of connection	Terminal, 3-Pole (L, N, PE)
Type of protection	IP44
Protection class IK (shock resistance)	IK03
Dimmable	no
Mounting type	Surface
Mounting location	Wall
Application environment	Outdoor
With light source	No
Holder designation	GU10

### EMERGENCY LIGHTING

Type of emergency light operation	Non-maintained
Luminous flux in maintained operation mode	-
Luminous flux in emergency operation mode	-





### CERTIFICATES & STANDARDS

Standards	CE / EAC / UKCA
Luminaire with limited surface temperature, "D sign"	No

### ADDITIONAL PRODUCT DATA

Product remark	Maximum bulb wattage: 2 x 35 W
Number of illuminants	1

### download\_data

Documents and certificates		document_name
	User instruction	ENDURA CLASSIC
	Packaging insert	Legal insert I-Outdoor
	Declarations Of Conformity CE	
	Declarations Of Conformity UKCA	Fixed LUM without EMC

### logistical\_data

product_code	packaging_unit	dimensions	weight	volume
4058075554573	Folding box 1	100 mm x 110 mm x 210 mm	867.00 g	2.31 dm <sup>3</sup>
4058075554580	Shipping box 4	245 mm x 220 mm x 235 mm	3813.00 g	12.67 dm <sup>3</sup>

logistical\_data\_text

---

disclaimer\_title

disclaimer\_text