

product_datasheet_title

LED Superstar Plus Classic P 40 Filament 4W 827 E14 3step DIM

LED THREE STEP DIM CLASSIC P | LED lamps with three-step dimming



technical_data

ELECTRICAL DATA

Nominal wattage	4 W
Construction wattage	4.00 W
Nominal voltage	220...240 V
Operating mode	AC Mains
Claimed equiv. conventional lamp power	40 W
Nominal current	36 mA
Type of current	AC
Inrush current	0,5 A
Operating frequency	50/60 Hz
Mains frequency	50/60 Hz
Max. lamp number on MCB B10 A	222
Max. lamp number on MCB B16 A	355
Power factor λ	≥ 0.40

PHOTOMETRICAL DATA

Luminous flux	470 lm
Luminous efficacy	117 lm/W
Lumen main.fact.at end of nom.life time	0.93
Light color (designation)	Warm White
Color temperature	2700 K
Color rendering index Ra	80
Light color	827
Standard deviation of color matching	≤ 6 sdc
Rated LLMF at 6,000 h	0.80
Flickering metric (Pst LM)	≤ 1.0
Stroboscope effect metric (SVM)	≤ 0.4



EPREL data spectral diagram PROF
LEDr 2700K

LIGHT TECHNICAL DATA

Beam angle	320 °
Warm-up time (60 %)	< 0.50 s
Starting time	< 0.5 s

DIMENSIONS & WEIGHT



Overall length	78.00 mm
Diameter	45.00 mm
Maximum diameter	45 mm
Product weight	13.00 g

TEMPERATURES & OPERATING CONDITIONS

Ambient temperature range	-20...+40 °C
Maximum temperature at tc test point	60 °C

LIFESPAN

Lifespan L70/B50 at 25 °C	15000 h
Number of switching cycles	100000
Lumen maintenance at end of service lifetime	0.93
Rated lamp survival factor at 6,000 h	≥ 0.90

ADDITIONAL PRODUCT DATA

Base (standard designation)	E14
Mercury content	0.0 mg
Mercury-free	Yes
Design / version	Clear
Product remark	All technical parameters apply to the entire lamp / Due to the complex production process for light-emitting diodes, the typical values shown for the technical LED parameters are purely statistical values that do not necessarily match the actual technical parameters of each individual product, which can vary from the typical value

CAPABILITIES

Dimmable	no
----------	----

CERTIFICATES & STANDARDS

Energy efficiency class	E ¹⁾
Energy consumption	4.00 kWh/1000h
Type of protection	IP20
Standards	CE / UKCA
Photobiological safety group acc. to EN62778	RG1

¹⁾ Energy efficiency class (EEC) on a scale of A (highest efficiency) to G (lowest efficiency)

COUNTRY-SPECIFIC CATEGORIZATIONS

Order reference	LEDSCLP403XD 4W
-----------------	-----------------

LOGISTICAL DATA




Temperature range at storage	-20...+80 °C
------------------------------	--------------

Energy labelling regulation data

Lighting technology used	LED
Non-directional or directional	NDLS
Mains or non-mains	MLS
Light source cap-type (or other electric interface)	E14
Connected light source (CLS)	no
Color-tunable light source	no
Envelope	No
High luminance light source	no
Anti-glare shield	no
Correlated colour temperature type	SINGLE_VALUE
Claim of equivalent power	Yes
Length	78.00 mm
Height	45.00 mm
Width	45.00 mm
Chromaticity coordinate x	0.463
Chromaticity coordinate y	0.420
R9 Colour rendering index	>0
Beam angle correspondence	SPHERE_360

Survival factor	0.90
LED light source replaces a fluorescent light source	no
EPREL ID	523113,1358091
Model number	AC32271,AC44586

download_data

Documents and certificates		document_name
	Declarations Of Conformity CE	LED lamps CLA,B,G,P
	Declarations Of Conformity CE	LED CLASSIC MAGNETIC
Photometric and lighting design files		document_name
	Spectral power distribution	EPREL data spectral diagram PROF LEDr 2700K

logistical_data

product_code	packaging_unit	dimensions	weight	volume
4058075434448	Folding box 1	46 mm x 49 mm x 130 mm	25.00 g	0.29 dm ³
4058075434455	Shipping box 4	111 mm x 110 mm x 104 mm	160.00 g	1.27 dm ³
4058075445277	Shipping box 32	240 mm x 238 mm x 237 mm	1530.00 g	13.54 dm ³

logistical_data_text

disclaimer_title

disclaimer_text