



product_datasheet_title

LS VAL -500/RGB/5

LED STRIP VALUE-500 RGB | RGB LED strips with 500 lm/m for general applications



technical_data

ELECTRICAL DATA

Nominal wattage	67.00 W
Construction wattage	67.00 W
Nominal wattage per meter	14.4 W ¹⁾
Nominal voltage	24 V ²⁾
Input voltage range	23...25 V ²⁾
Reverse Voltage	27 V ²⁾
Type of current	DC
Nominal current	2800 mA

1) Value based on first meter of the product

2) V_{DC}

PHOTOMETRICAL DATA

Luminous efficacy	37.2 lm/W ¹⁾
Luminous flux	2400 lm
Luminous flux per meter	535 lm ¹⁾
Luminous flux per module chain	2400 lm
Luminous flux per meter - Red	106 lm/m ¹⁾
Luminous flux per meter - Green	325 lm/m ¹⁾
Luminous flux per meter - Blue	73 lm/m ¹⁾
Luminous flux per meter - RGB	535 lm/m ¹⁾
Light color LED	RGB
Light color (designation)	RGB

1) Value based on first meter of the product


LIGHT TECHNICAL DATA

Beam angle	120 °
Rated beam angle (half peak value)	120.00 °

LED MODULE INFORMATION

Number of LEDs per meter	60
Number of LEDs per module	300
Number of LEDs per smallest unit	6

DIMENSIONS & WEIGHT



Length	5000.00 mm
Length – smallest unit	100 mm
Cable length	500.000
Width	10.00 mm
Height	2.20 mm
Prewired	Yes
Conductor cross section	0.5 mm ²
LED pitch	16.7 mm
Short pitch	No
Product weight	110.00 g

TEMPERATURES & OPERATING CONDITIONS

Ambient temperature range	-20...+45 °C ¹⁾
Maximum temperature at tc test point	75 °C ²⁾

1) Providing that temperature at Tc point is below max value during operation

2) Exceeding the maximum specified ratings can reduce expected life time or destroy the LED strip

LIFESPAN

Nominal lamp life time	40000 h
------------------------	---------

CAPABILITIES

Dimmable	yes ¹⁾
Lowest bending radius	30 mm
Self-adhesive	Yes

1) Dimmable with suitable drivers, see also www.ledvance.com/dim

CERTIFICATES & STANDARDS








Approval marks – approval	RoHS / CE / REACH
Protection class	III
Type of protection	IP00

Salt mist resistance acc. IEC 60068-2-52	No
UV resistance acc. IEC 60068-2-5	No












LOGISTICAL DATA












Temperature range at storage	-20...+85 °C
------------------------------	--------------




Accessories Mandatory

product_image	product_name	product_ean
	DR-PFM -150/220-240/24/P	4058075239975
	DR-PFM -250/220-240/24/P	4058075240032
	DR-VAL -150/220-240/24	4058075240179
	DR-VAL -120/220-240/24	4058075240131
	DR DIM-PFM -150/220-240/24/P	4058075240117
	DR DIM-PFM -100/220-240/24/P	4058075240070
	DR-PFM -100/220-240/24/P	4058075239937
	DR DIM-PFM -250/220-240/24/P	4058075240155



Accessories Optional

product_image	product_name	product_ean
	LS AY -PF04/U/17X7/12/1	4058075278288
	LS AY -PW02/UW/39X26/14/1	4058075278134
	LS AY -PM03/E/19X19/10/2	4058075401716
	LS AY -PM06/E/18X18/12/2	4058075401808
	LS AY -PM02/R/18X15,5/10/2	4058075401686
	LS AY -PW01/U/26X8/14/1	4058075278103
	LS AY -PM01/UW/21,5X12/10/1	4058075278318
	LS AY -PM03/E/19X19/10/1	4058075278370
	LS AY -PF02/U/16X5/10/2	4058075401563
	LS AY -PF04/U/17X7/12/2	4058075401624
	LS AY VAL -CSD/P4	4058075407831

product_image	product_name	product_ean
	LS AY -PM04/UW/23X15,5/10/1	4058075278400
	LS AY -PW03/U/26X26/14/1	4058075278165
	LS AY -PM06/E/18X18/12/1	4058075279308
	LS AY -PM04/UW/23X15,5/10/2	4058075401747
	LS AY -PF01/UW/22X6/10/1	4058075278196
	LS AY -PM01/UW/21,5X12/10/2	4058075401655
	LS AY -PM02/R/18X15,5/10/1	4058075278349
	LS AY -PM05/U/17,5X14,5/10/2	4058075401778
	LS AY VAL -12/SMB	4058075411708
	LS AY -PW01/U/26X8/14/2	4058075401440
	LS AY -PF01/UW/22X6/10/2	4058075401532

product_image	product_name	product_ean
	LS AY -PW03/U/26X26/14/2	4058075401501
	LS AY -PF03/UW/25X7/12/2	4058075401594
	LS AY VAL -CSW/P4/50	4058075407862
	LS AY VAL -CP/P4/500	4058075407800
	LS AY -PF02/U/16X5/10/1	4058075278226
	LS AY -PW02/UW/39X26/14/2	4058075401471
	LS AY -PF03/UW/25X7/12/1	4058075278257
	LS AY -PM05/U/17,5X14,5/10/1	4058075279278

download_data

Documents and certificates	document_name
 User instruction	LED STRIP VALUE RGB IP00
 Declarations Of Conformity CE	LS VAL RGB

Photometric and lighting design files	document_name
 IES file (IES)	LS VAL-500-RGB-5-1M-RGB_IESNA2002
 IES files (IES, additional)	LS VAL-500-RGB-5-1M-Blue_IESNA2002
 IES files (IES, additional)	LS VAL-500-RGB-5-0.1M-Red_IESNA2002
 IES files (IES, additional)	LS VAL-500-RGB-5-0.1M-Blue_IESNA2002
 IES files (IES, additional)	LS VAL-500-RGB-5-1M-Red_IESNA2002
 IES files (IES, additional)	LS VAL-500-RGB-5-1M-Green_IESNA2002
 IES files (IES, additional)	LS VAL-500-RGB- 5-0.1M-Green_IESNA2002
 IES files (IES, additional)	LS VAL-500-RGB-5-0.1M-RGB_IESNA2002
 LDT file (Eulumdat)	LS VAL-500-RGB-5-1M-RGB
 LDT files (Eulumdat, additional)	LS VAL-500-RGB-5-1M-Red
 LDT files (Eulumdat, additional)	LS VAL-500-RGB-5-1M-Green
 LDT files (Eulumdat, additional)	LS VAL-500-RGB-5-0.1M-RGB
 LDT files (Eulumdat, additional)	LS VAL-500-RGB-5-0.1M-Blue
 LDT files (Eulumdat, additional)	LS VAL-500-RGB-5-1M-Blue
 LDT files (Eulumdat, additional)	LS VAL-500-RGB-5-0.1M-Red
 LDT files (Eulumdat, additional)	LS VAL-500-RGB-5-0.1M-Green

logistical_data

product_code	packaging_unit	dimensions	weight	volume
--------------	----------------	------------	--------	--------

product_code	packaging_unit	dimensions	weight	volume
4058075404441	Folding box 1	242 mm x 242 mm x 26 mm	301.00 g	1.52 dm ³
4058075404458	Shipping box 10	260 mm x 260 mm x 265 mm	3401.00 g	17.91 dm ³
4058075404465	Shipping box 40	540 mm x 280 mm x 555 mm	13604.00 g	83.92 dm ³

logistical_data_text

disclaimer_title

disclaimer_text